

TERMINAL BOARD



CS-N7



CS-L7



CS-PE12

- For branching or connection of PEN, PE, N and L conductors.
- They are used in switchboards, which are not delivered with terminal blocks.
- Completely covered.
- Fastening on the "U" rail wide 35 mm according to EN 60715.
- Colour: green, blue, grey.


Colour	Number of terminals	Type	Order code	Weight [kg]	Package [pcs]
blue	7x 16 mm ²	CS-N7	OEZ:35901	0.026	10
	12x 16 mm ²	CS-N12	OEZ:35902	0.030	10
	15x 16 mm ²	CS-N15	OEZ:35903	0.048	10
green	7x 16 mm ²	CS-PE7	OEZ:35904	0.026	10
	12x 16 mm ²	CS-PE12	OEZ:35905	0.030	10
	15x 16 mm ²	CS-PE15	OEZ:35906	0.048	10
grey	7x 16 mm ²	CS-L7	OEZ:35898	0.026	10
	12x 16 mm ²	CS-L12	OEZ:35899	0.030	10
	15x 16 mm ²	CS-L15	OEZ:35900	0.048	10

Specifications


Type	CS-PE, CS-N, CS-L
Standards	EN 60998-1
Approval marks	CE EAC
Rated current	63 A
Mounting on "U" rail according to EN 60715 – type	TH 35
Connection - conductor Cu	1 ÷ 16 mm ²
Torque	1.5 ÷ 2 Nm
Ambient temperature	-25 ÷ +60 °C

Dimensions

CS-...N7



CS-...N12



CS-...N15

